

New Budget-friendly 7" Indoor Monitors

Powered by **ANDROID**



Akuvox C315N Android Indoor Monitor

- 7" touch screen with 1024 x 600 resolution
- Powered by PoE or external source
- Doorbell button support
- SIP-based communications
- Support 3rd-party apps

Compare C315N with C315S

Model	C315N	C315S
OS	Android	
Cover	Glass surface and touch screen	
Display	7 inch active matrix TFT, transmissive type	
Wifi & Bluetooth	NA	
Ethernet	1 x 10/100 Mbps RJ45	2 x 10/100 Mbps RJ45
Power Supply	12V/1A or PoE 802.3af	
Alarm Input	NA	8 x Alarm Inputs
Door Bell Input	1 x Bell In	
RS485	NA	1 x RS485(485+/485-)
Relay Output	NA	1 x Relay Out(NO/COM/NC)
RTC Real Time Clock	NA	1 x RTC
Installation	Wall-mounted with on-wall mounting bracket	
Operating Temperature	32° to 113°F (0° to 45°C)	
Operating Humidity	10% to 90% (non-condensing)	
Dimensions(W x H x D)	200 x 132 x 17.5 mm	

Akuvox C313N Linux Indoor Monitor

- 7" touch screen with 800 x 480 resolution
- Powered by PoE or external source
- Doorbell button support
- SIP-based communications



Compare C313N with C313S

Model	C313N	C313S
OS	Linux	
Cover	Glass surface and touch screen	
Display	7 inch active matrix TFT, transmissive type	
Wifi & Bluetooth	NA	
Ethernet	1 x 10/100 Mbps RJ45	2 x 10/100 Mbps RJ45
Power Supply	12V/1A or PoE 802.3af	
Alarm Input	NA	8 x Alarm Inputs
Door Bell Input	1 x Bell In	
RS485	NA	1 x RS485(485+/485-)
Relay Output	NA	1 x Relay Out(NO/COM/NC)
RTC Real Time Clock	NA	1 x RTC
Installation	Wall-mounted with on-wall mounting bracket	
Operating Temperature	32° to 113°F (0° to 45°C)	
Operating Humidity	10% to 90% (non-condensing)	
Dimensions(W x H x D)	200 x 132 x 17.5 mm	



Akuvox



10/F, No.56 Guanri Road, Software Park II, Xiamen 361009, China
Tel: +86-592-2133061 Ext: 7694/8162 Fax: +86-592-2133061
Email: sales@akuvox.com Web: www.akuvox.com



Contact Us